

Package: gwavr (via r-universe)

September 7, 2024

Title Get Water Attributes Visually in R

Version 0.3.1

Description Provides methods to Get Water Attributes Visually in R ('gwavr'). This allows the user to point and click on areas within the United States and get back hydrological data, e.g. flowlines, catchments, basin boundaries, comids, etc.

URL <https://github.com/joshualerickson/gwavr/>

BugReports <https://github.com/joshualerickson/gwavr/issues/>

License MIT + file LICENSE

Encoding UTF-8

Roxygen list(markdown = TRUE)

RoxygenNote 7.3.1

Imports dplyr, httr, jsonlite, leaflet, leaflet.extras, nhdplusTools, purrr, scales, sf, shiny, promises, miniUI, shinyWidgets, tidyrr, units, utils, elevatr, whitebox, terra, htmlwidgets

Suggests spelling, knitr, rmarkdown, testthat (>= 3.0.0)

Language en-US

Config/testthat/edition 3

LazyData true

Repository <https://joshualerickson.r-universe.dev>

RemoteUrl <https://github.com/joshualerickson/gwavr>

RemoteRef HEAD

RemoteSha 5ea1b041cd5f8baaaf15ec62b0ad052a3dece784

Contents

base_map	2
basinMod	2
basinModUI	3

convert_sf_geocollection	4
df_site_new	4
get_basin_interactively	5
get_nhdplus_interactively	6
get_nldi_interactively	7
get_stream_network_interactively	8
get_usgs_dv_interactively	10
get_usgs_iv_interactively	11
nhdplusMod	12
nhdplusModUI	13
rename_geometry	13
streamnetworkMod	14
streamnetworkModUI	15
usgsdvMod	15
usgsdvModUI	16
usgsinstMod	16
usgsinstModUI	17

Index **18**

base_map	<i>Base Map</i>
----------	-----------------

Description

A generic leaflet base map used in the shiny apps.

Usage

base_map()

Value

A leaflet map with provider layers: **"Esri.WorldImagery"**, **"CartoDB.Positron"**, **"OpenStreetMap"**, **"CartoDB.DarkMatter"**, **"OpenTopoMap"** **"Hydrography"**

basinMod	<i>Shiny Module Server for basin generation</i>
----------	---

Description

Shiny Module Server for basin generation

Usage

basinMod(input, output, session, values, dem, threshold = 1000, map, ...)

Arguments

input	Shiny server function input
output	Shiny server function output
session	Shiny server function session
values	A reactive Values list to pass
dem	A raster or terra object dem.
threshold	A threshold for stream initiation. 1000 (default).
map	a background leaflet or mapview map to be used for editing. If NULL a blank mapview canvas will be provided.
...	arguments to pass to wbt_* functions.

Value

server function for Shiny module

 basinModUI

Shiny Module UI for basin generation

Description

A shiny Module to.

Usage

```
basinModUI(id, ...)
```

Arguments

id	character id for the the Shiny namespace
...	other arguments to leafletOutput()

Value

UI function for Shiny module

```
convert_sf_geocollection
```

Convert GEOMETRYCOLLECTION to POLYGONS

Description

Convert GEOMETRYCOLLECTION to POLYGONS

Usage

```
convert_sf_geocollection(x)
```

Arguments

x A sf object

Value

A converted sf object from GEOMETRYCOLLECTION to POLYGON or MULTIPOLYGON.

```
df_site_new
```

Retired USGS Sites

Description

A subset of data that has retired USGS sites and coordinates.

Usage

```
df_site_new
```

Format

df_site_new:

A data frame with 14,966 rows and 4 columns:

SiteNumber Site Number

SiteName Site Name

location.coordinates1 Longitude coordinates

location.coordinates2 Latitude coordinates ...

`get_basin_interactively`*Get Watershed Basin Interactively*

Description

This function allows the user to delineate watershed basins interactively with a shiny app. It uses the `elevatr` package to acquire the Digital Elevation Model (DEM) or user inputted DEM and `whitebox` package to delineate the basin (see details).

Usage

```
get_basin_interactively(  
  map = NULL,  
  ns = "basin-ui",  
  viewer = shiny::paneViewer(),  
  title = "Delineate Basin",  
  dem = NULL,  
  threshold = 1000,  
  ...  
)
```

Arguments

<code>map</code>	a background leaflet or mapview map to be used for editing. If <code>NULL</code> a blank mapview canvas will be provided.
<code>ns</code>	string name for the Shiny namespace to use. The <code>ns</code> is unlikely to require a change.
<code>viewer</code>	function for the viewer. See Shiny viewer . NOTE: when using <code>browserViewer(browser = getOption("browser"))</code> to open the app in the default browser, the browser window will automatically close when closing the app (by pressing "done" or "cancel") in most browsers. Firefox is an exception. See Details for instructions on how to enable this behaviour in Firefox.
<code>title</code>	string to customize the title of the UI window. The default is "Delineate Basin".
<code>dem</code>	A 'SpatRaster' object <code>dem</code> . (optional)
<code>threshold</code>	A threshold for stream initiation. 1000 (default).
<code>...</code>	other arguments to <code>leafletOutput()</code> in module and/or <code>wbt_*</code> functions.

Details

This function will throw an error if you don't draw the bounding box (rectangle) first and you didn't include your own DEM. Once the user has drawn the bounding box (or added own DEM) then you can use the marker as a pour point location.

Steps

1. Input a well-suited DEM zoom level and threshold. (skip if own DEM is inputted)
2. Draw bounding box (rectangle or polygon) (skip if own DEM is inputted).
3. Use marker to place pour point(s).
4. If necessary, change 'Cell Threshold' to change drainage density.
5. Repeat steps 1-4 if needed.
6. When finished, press 'done' and basins will be saved as a list in local environment.

In addition, this function uses both `whitebox::wbt_feature_preserving_smoothing()` and `whitebox::wbt_breach_dep` prior to running the flow direction and flow accumulation (both d8) algorithms.

Value

A sf object that contains watershed polygons the user collected during shiny session.

Note

The marker will only work for the most current stream raster. You can have multiple areas but you need to make sure that you are on the most current raster when selecting basins or the app will crash. If you add your own DEM then you don't need to draw a bounding box.

Examples

```
if(interactive()){  
  basin_data <- get_basin_interactively()  
}
```

`get_nhdplus_interactively`
Get NHDPlus Interactively

Description

This function allows the user go get NHDPlus realizations interactively with a shiny app.

Usage

```
get_nhdplus_interactively(  
  ns = "hydro-ui",  
  viewer = shiny::paneViewer(),  
  title = "NHDPlus",  
  ...  
)
```

Arguments

ns	string name for the Shiny namespace to use. The ns is unlikely to require a change.
viewer	function for the viewer. See Shiny viewer . NOTE: when using <code>browserViewer(browser = getOption("browser"))</code> to open the app in the default browser, the browser window will automatically close when closing the app (by pressing "done" or "cancel") in most browsers. Firefox is an exception. See Details for instructions on how to enable this behaviour in Firefox.
title	string to customize the title of the UI window. The default is "NHDPlus".
...	other arguments to <code>leafletOutput()</code> in module.

Value

A list of sf objects that the user collected during shiny session.

Note

The picker list has several options right now: NHDPlus Catchments, NHDPlus Flowlines, NHDPlus Waterbodies, NHDPlus Outlet, HUC 2-12, NWIS Site.

Examples

```
if(interactive()){  
  nhdplus_data <- get_nhdplus_interactively()  
}
```

get_nldi_interactively

Get Hydro Network-Linked Data Index (NLDI) Interactively

Description

This function uses the NLDI API to allow the user to visually select a location (point) to get numerous hydrologic realizations.

Usage

```
get_nldi_interactively()
```

Value

A list with sf objects.

Note

The picker list has three options right now: Total Basin, All Local Catchments and Only Local Catchment. Descriptions below:

- **Total Basin:** This will return the upstream tributaries (UT), upstream main (UM), basin boundary and site data above the user point.
- **All Local Catchments:** This will return the upstream tributaries (UT) and all the local NHD-PlusV2 catchments above the user point. In addition, each catchment will contain the zonal stats associated with 'CAT' in NLDI.
- **Only Local Catchment:** This will only return the catchment at the point and tributary. In addition, it will also include the zonal stat for that catchment.

Examples

```
if(interactive()){
  nldi_data <- get_nldi_interactively()
}
```

```
get_stream_network_interactively
      Get Stream Network Interactively
```

Description

This function allows the user to get stream networks and watersheds interactively with a shiny app. It uses the elevatr package to acquire the Digital Elevation Model (DEM) or user inputted DEM and whitebox package to delineate the stream network and watersheds (see details).

Usage

```
get_stream_network_interactively(
  map = NULL,
  ns = "streamnetwork-ui",
  viewer = shiny::paneViewer(),
  title = "Streamnetwork",
  dem = NULL,
  threshold = 1000,
  ...
)
```

Arguments

map	a background leaflet or mapview map to be used for editing. If NULL a blank mapview canvas will be provided.
ns	string name for the Shiny namespace to use. The ns is unlikely to require a change.

viewer	function for the viewer. See Shiny viewer . NOTE: when using <code>browserViewer(browser = getOption("browser"))</code> to open the app in the default browser, the browser window will automatically close when closing the app (by pressing "done" or "cancel") in most browsers. Firefox is an exception. See Details for instructions on how to enable this behaviour in Firefox.
title	string to customize the title of the UI window. The default is "Delineate Basin".
dem	A raster or terra object dem. (optional)
threshold	A threshold for stream initiation. 1000 (default).
...	other arguments to <code>leafletOutput()</code> in module and/or <code>wbt_*</code> functions.

Details

This function uses the package [elevatr](#) to download the DEM (unless you provide your own). Once the user has drawn the bounding box or inputted DEM and selected appropriate zoom (resolution) and threshold then the app will create basins and streams.

Steps

1. Input a well-suited DEM zoom level and threshold. (skip if own DEM is inputted)
2. Draw bounding box (rectangle or polygon) (skip if own DEM is inputted).
3. Wait for layers to respond.
4. Repeat steps 1-4 if needed.
5. when finished, press 'done' and stream network and watersheds will be saved as a list in local environment with the associated flow accumulation and flow direction.

In addition, this function uses both `whitebox::wbt_feature_preserving_smoothing()` and `whitebox::wbt_breach_dep` prior to running the flow direction and flow accumulation (both d8) algorithms.

Value

A list of sf objects that the user collected during shiny session as well as flow accumulation and direction paths to tif. Each list will contain two sf objects: watersheds and streams. The streams object will also return these attributes: `tribid`, `strahler`, `slope`, `length`, `mainstem`, `FID`, `STRM_VAL`.

Note

If you add your own DEM then you don't need to draw a bounding box.

Examples

```
if(interactive()){
  streamnetwork <- get_stream_network_interactively()
}
```

`get_usgs_dv_interactively`*Get United States Geologic Survey (USGS) Daily Flow Values Interactively*

Description

This function allows the user to select United States Geologic Survey (USGS) stations and get back daily flow values based on station selected. It uses the USGS Water Services to get the values as well as the USGS Sites.

Usage

```
get_usgs_dv_interactively(  
  ns = "usgsdv-ui",  
  viewer = shiny::paneViewer(),  
  title = "Get USGS Daily Flow Values",  
  ...  
)
```

Arguments

<code>ns</code>	string name for the Shiny namespace to use. The <code>ns</code> is unlikely to require a change.
<code>viewer</code>	function for the viewer. See Shiny viewer . NOTE: when using <code>browserViewer(browser = getOption("browser"))</code> to open the app in the default browser, the browser window will automatically close when closing the app (by pressing "done" or "cancel") in most browsers. Firefox is an exception. See Details for instructions on how to enable this behaviour in Firefox.
<code>title</code>	string to customize the title of the UI window. The default is "Get USGS Instantaneous Flow Values".
<code>...</code>	other arguments to <code>leafletOutput()</code> in module.

Details

Steps

1. Select the sites you want to retrieve.
2. When finished, press 'done' and sites daily flow values will be saved to a data.frame in local environment.

Value

A data.frame that contains flow values based on the station(s) selected during shiny session.

Note

You can select multiple stations. The information from the hover details is not included in the data.frame that is returned, e.g. rate of change, percentile description.

Examples

```
if(interactive()){
  dv_usgs <- get_usgs_dv_interactively()
}
```

```
get_usgs_iv_interactively
```

Get United States Geologic Survey (USGS) Instantaneous Flow Values Interactively

Description

This function allows the user to select United States Geologic Survey (USGS) stations and get back instantaneous flow values based on control number of days from now. It uses the USGS Water Services to get the values as well as the USGS Dashboard to get current conditions (circle markers on map).

Usage

```
get_usgs_iv_interactively(
  ns = "usgsiv-ui",
  viewer = shiny::paneViewer(),
  title = "Get USGS Instantaneous Flow Values",
  ...
)
```

Arguments

ns	string name for the Shiny namespace to use. The ns is unlikely to require a change.
viewer	function for the viewer. See Shiny viewer . NOTE: when using <code>browserViewer(browser = getOption("browser"))</code> to open the app in the default browser, the browser window will automatically close when closing the app (by pressing "done" or "cancel") in most browsers. Firefox is an exception. See Details for instructions on how to enable this behaviour in Firefox.
title	string to customize the title of the UI window. The default is "Get USGS Instantaneous Flow Values".
...	other arguments to <code>leafletOutput()</code> in module.

Details**Steps**

1. Select the sites you want to retrieve.
2. Make sure you have the right days.
3. When finished, press 'done' and sites instantaneous flow values will be saved to a data.frame in local environment.

Value

A data.frame that contains flow values based on the station(s) selected during shiny session.

Note

You can select multiple stations but the number of days from now control will take the final number when you select the done button. The information from the hover details is not included in the data.frame that is returned, e.g. rate of change, percentile description.

Examples

```
if(interactive()){  
  iv_usgs <- get_usgs_iv_interactively()  
}
```

nhdplusMod

Shiny Module Server for nhdplus

Description

Shiny Module Server for nhdplus

Usage

```
nhdplusMod(input, output, session, values)
```

Arguments

input	Shiny server function input
output	Shiny server function output
session	Shiny server function session
values	A reactive Values list to pass

Value

server function for Shiny module

nhdplusModUI	<i>Shiny Module UI for nhdplus</i>
--------------	------------------------------------

Description

A shiny Module to.

Usage

```
nhdplusModUI(id, ...)
```

Arguments

id	character id for the the Shiny namespace
...	other arguments to leafletOutput()

Value

UI function for Shiny module

rename_geometry	<i>Rename Geometry Column</i>
-----------------	-------------------------------

Description

Rename Geometry Column

Usage

```
rename_geometry(g, name)
```

Arguments

g	A sf object
name	character.

Value

A sf object with a renamed geometry column.

Note

This function was grabbed from [stack overflow](#) from the legend spacedman.

streamnetworkMod *Shiny Module Server for stream networks*

Description

Shiny Module Server for stream networks

Usage

```
streamnetworkMod(  
  input,  
  output,  
  session,  
  values,  
  dem,  
  threshold = 1000,  
  map,  
  ...  
)
```

Arguments

input	Shiny server function input
output	Shiny server function output
session	Shiny server function session
values	A reactive Values list to pass
dem	A raster or terra object dem. (optional)
threshold	A threshold for stream initiation. 1000 (default).
map	a background leaflet or mapview map to be used for editing. If NULL a blank mapview canvas will be provided.
...	arguments to pass to wbt_* functions.

Value

server function for Shiny module

streamnetworkModUI	<i>Shiny Module UI for stream network generation</i>
--------------------	--

Description

A shiny Module to.

Usage

```
streamnetworkModUI(id, ...)
```

Arguments

id	character id for the the Shiny namespace
...	other arguments to leafletOutput()

Value

UI function for Shiny module

usgsdvMod	<i>Shiny Module Server for United States Geologic Survey (USGS) daily values</i>
-----------	--

Description

Shiny Module Server for United States Geologic Survey (USGS) daily values

Usage

```
usgsdvMod(input, output, session, values)
```

Arguments

input	Shiny server function input
output	Shiny server function output
session	Shiny server function session
values	A reactive Values list to pass

Value

server function for Shiny module

usgsdvModUI	<i>Shiny Module UI for United States Geologic Survey (USGS) daily values</i>
-------------	--

Description

A shiny Module to.

Usage

```
usgsdvModUI(id, ...)
```

Arguments

id	character id for the the Shiny namespace
...	other arguments to leafletOutput()

Value

UI function for Shiny module

usgsinstMod	<i>Shiny Module Server for United States Geologic Survey (USGS) instantaneous values</i>
-------------	--

Description

Shiny Module Server for United States Geologic Survey (USGS) instantaneous values

Usage

```
usgsinstMod(input, output, session, values)
```

Arguments

input	Shiny server function input
output	Shiny server function output
session	Shiny server function session
values	A reactive Values list to pass

Value

server function for Shiny module

usgsinstModUI	<i>Shiny Module UI for United States Geologic Survey (USGS) instantaneous values</i>
---------------	--

Description

A shiny Module to.

Usage

```
usgsinstModUI(id, ...)
```

Arguments

id	character id for the the Shiny namespace
...	other arguments to leafletOutput()

Value

UI function for Shiny module

Index

* datasets

df_site_new, [4](#)

base_map, [2](#)

basinMod, [2](#)

basinModUI, [3](#)

convert_sf_geocollection, [4](#)

df_site_new, [4](#)

elevatr, [9](#)

get_basin_interactively, [5](#)

get_nhdplus_interactively, [6](#)

get_nldi_interactively, [7](#)

get_stream_network_interactively, [8](#)

get_usgs_dv_interactively, [10](#)

get_usgs_iv_interactively, [11](#)

nhdplusMod, [12](#)

nhdplusModUI, [13](#)

rename_geometry, [13](#)

streamnetworkMod, [14](#)

streamnetworkModUI, [15](#)

usgsdvMod, [15](#)

usgsdvModUI, [16](#)

usgsinstMod, [16](#)

usgsinstModUI, [17](#)

viewer, [5](#), [7](#), [9–11](#)